

FGDH and FGPDH Full-Coverage Drum Heater

Drum Heater Highlights

- ✓ Full-coverage of drum
- ✓ Highest wattage available
- ✓ Grounded heating element meets NEC 427.23
- ✓ Easy to use digital temperature controller with audible / visual alarm
- ✓ Designed for metal or poly drums
- ✓ CE (see page A-2 for more information)

Temperatures up to



450°F (232°C)



Easily control temperatures with the programmable digital controller.

Display is mounted on top of controller box for increased visibility and user convenience.

Specifications

- Silicone impregnated cloth facing and liner
- 1" (25mm) fiberglass insulation
- Digital on/off temperature controller
 - 50-450°F (10-232°C) for metal drums
 - 50-160°F (10-71°C) for poly drums
- Heated area: FGDH: Lower third
 FGPDH: Lower two thirds
- Patented grounded heating element
- Dielectric strength over 2000 volts
- Closure: Hook and loop fastener like VELCRO®
- Power cord 6 feet (1.8m) long
- 500°F (260°C) maximum exposure on heating surface
- Designed for indoor use.

Ordering Information

For Metal Drums (FGDH Series)

Gallon Size	Diameter in (mm)	Total Wattage	Part Number 120VAC	Part Number 240VAC
55	22.3 (565)	1600	FGDHC55150D	FGDHC55240D

For Poly Drums (FGPDH Series)

Gallon Size	Diameter in (mm)	Total Wattage	Part Number 120VAC	Part Number 240VAC
55	22.3 (565)	770	FGPDHC55120D	FGPDHC55240D

Accessories

Part Number	Description
FGDC55	Drum Insulation Cover for 55 gallon. Further reduces heat loss.
FGDHSTRIP	6" (152mm) wide strip that expands heater to fit up to a 24.2" (615mm) diameter drum.

