


HXFL SERIES, LOW PROFILE L-SHAPED FLUOROPOLYMER (PTFE) HEATERS							
WATTS	VOLTS (See Pg.1)	HORIZ.	STD. VERT.	DIA.	MAX. COLD ZONE	MODEL NUMBER	SHIP WGT. Lbs./ (kg)
		LENGTH In./ (mm)	LENGTH* In./ (mm)				
500	120	5	12	5	36	HXFL.5105-R*.**	6
	240	(125)	(305)	(125)	(915)	HXFL.5205-R*.**	(2.5)
1000	120	6	12	6	36	HXFL1106-R*.**	7
	240	(155)	(305)	(155)	(915)	HXFL1206-R*.**	(3.5)
2000	120	8	18	8	35	HXFL2108-R*.**	8
	240	(205)	(460)	(205)	(890)	HXFL2208-R*.**	(4)
	480					HXFL2408-R*.**	
3000	240	9	18	9	35	HXFL3209-R*.**	13
	480	(230)	(460)	(230)	(890)	HXFL3409-R*.**	(6)
4000	240	11	18	11	35	HXFL4211-R*.**	15
	480	(280)	(460)	(280)	(890)	HXFL4411-R*.**	(7)
5000	240	12	18	12	31	HXFL5212-R*.**	18
	480	(305)	(460)	(305)	(790)	HXFL5412-R*.**	(8)
6000	240	13	18	13	25	HXFL6213-R*.**	22
	480	(330)	(460)	(330)	(635)	HXFL6413-R*.**	(10)

Single phase only. Guards recommended. This configuration is not recommended for electroless chemistry, phosphoric acid, or applications prone to sludge development.

Product Features and Benefits:

- ◆ **SUPERIOR CHEMICAL RESISTANCE:** Inert to most aqueous acid, alkaline, anodizing and pickling solutions up to 212°F (100°C).
- ◆ **RUGGED CONSTRUCTION:** Heavy wall fluoropolymer (PTFE) covered stainless steel element reduces permeation and eliminates the need for gas purge systems. Guaranteed 100% pinhole free.
- ◆ **OUTSTANDING PERFORMANCE:** Low watt density design (10 watts/square inch, 1.5w/cm²) for long service life.
- ◆ **EVEN HEATING:** Flat, low profile bottom design for even heating and varying liquid levels. (This configuration not recommended for electroless chemistry).
- ◆ **CORROSION RESISTANT HEAD:** Vapor tight, flame retardant polypropylene terminal enclosure with 3-foot (.9m) flexible PVC liquid tight conduit.
- ◆ **SAFETY FEATURES:**
 - Grounded internal metal element.
 - Thermal protector built in. Replaceable PTL-I fuse standard for solutions up to 190°F (88°C).
 - Non-floating construction.
- ◆ **CERTIFICATIONS:** UL, CSA, and CE.
- ◆ **SIZES:** 500 watts to 6,000 watts.
- ◆ **VOLTAGES:** 120, 240 or 480 volts. 208, 380, 415, 600 and other voltages available. Single phase only.
- ◆ **OPTIONS AVAILABLE** (consult factory):
 - Replaceable thermal protectors:
 - PTL-IM: for solutions from 190°F (88°C) to 220°F (104°C).
 - Resettable thermal protectors:
 - PTL-II: bi-metal switch for solutions up to 190°F (88°C).
 - PTL-III: type-J thermocouple for solutions from 190°F (88°C) to 210°F (99°C).
 - PIII: type-J thermocouple for solutions from 210°F (99°C) to 250°F (121°C).
 - Longer vertical lengths (cold zones).
 - Polypropylene guards: recommended for applications up to 180°F (82°C).
 - Fluoropolymer (PTFE) guards: recommended for chromic acid or solutions over 180°F (82°C).
 - Special configurations.
 - Longer wire and conduit lengths.
 - Flexible continuous fluoropolymer leads (PIII protector only).
 - Lower watt densities for highly viscous solutions and technical acids.
 - Temperature and level controls sized to match the heater.

DIMENSIONS



LOW PROFILE L-SHAPED FLUOROPOLYMER (PTFE) HEATER

Series	Wattage	Voltage	Diameter	Options	Vertical Length	Guard Option	Type of Fuse	Wire and Conduit Length
	.5 = 500 1 = 1000 2 = 2000 3 = 3000 4 = 4000 5 = 5000 6 = 6000	1 = 120 2 = 240 4 = 480 -208- = 208 -277- = 277 -380- = 380 -415- = 415 -600- = 600	05 = .5kW 06 = 1kW 08 = 2W 09 = 3kW 11 = 4kW 12 = 5kW 13 = 6kW		-R12 = .5kW -R12 = 1kW -R18 = 2kW -R18 = 3kW -R18 = 4kW -R18 = 5kW -R18 = 6kW specify custom lengths, not to exceed tank length			no designator = 36" length standard specify variations from standard Ex: -X84 = 84"
	HXFL = PTFE sheathed HSFL = 304 stainless steel						Replaceable Fuse	
							-PTL-I (std) for solutions up to 190°F -PTL-IM for 190° - 220°F solutions	
							Resettable Fuse	
							(additional control components required)	
							-PTL-II for solutions up to 190°F -PTL-III for 190° - 210°F solutions -PIII for 210° - 250°F solutions	
								C = complete with guard
	X = any special configuration not called out in the part number (specify in clear text)							

ORDERING EXAMPLE:

HXFL5412-R18-PTL-I-X50

Flat L-Shaped fluoropolymer heater, 5000 watts, 480 volt, single phase, 12" diameter hot zone, 18" vertical length, PTL-I thermal fuse, 50" wire and conduit

O.E.M. HEATERS

www.oemheaters.com

Toll Free: (866) 685-4443

Email: info@oemheaters.com